

PRODUCT DATA SHEET

HSB74 Stack Bag

Specifications

article number		151.000.950
model		HSB74
short description		Stack Bag
max. working pressure	bar	12
max. inflation height	mm	170
thickness incl. profile	mm	27
max. lifting capacity	kN/t	724 / 73.8
max. lifting capacity (12 bar/174 psi)	kN/t	724 / 73.8
max. lifting capacity (8 bar/116 psi)	kN/t	483 / 49.3
lifting capacity at insertion height plus 25 mm / 1 in. (12 bar /174 psi)	kN/t	658 / 67.1
lifting capacity at insertion height plus 25 mm / 1 in. (8 bar /116 psi)	kN/t	439 / 44.8
lifting capacity at max. lifting height (12 bar/174 psi)	kN/t	370 / 37.7
lifting capacity at max. lifting height (8 bar/116 psi)	kN/t	246 / 25.1
air content (12 bar/174 psi)	l	833
air content (8 bar/116 psi)	l	555
connection		ISO 6150 C
min. bursting pressure	bar/Mpa	48 / 4.8
material		reinforced with 2 aramide inlays
weight, ready for use	kg	23.8
dimensions (AxBxC)	mm	840 x 840 x 27
temperature range	°C	-20 + 55
EN 13731 compliant		yes
NFPA 1936 compliant		yes

Required Accessories

Control Unit HTC12	151.002.137
Shut-Off Hose SOH 12	350.182.096
Pressure Reducer PRV 12	350.182.100
Air Hose AH 5 Y	350.570.022
Air Hose AH 5 B	350.570.023
Air Hose AH 10 B	350.570.026
Air Hose AH 10 Y	350.570.027
Air Hose AH 5 O	350.570.030
Air Hose AH 10 O	350.570.031
Pressure Reducer PRV 12 CGA346	358.182.000
Pressure Reducer PRV 12 HP	358.182.001
Shut-Off Hose SOH 174	358.570.007
Air Bottle 300 Bar	350.581.096
Air Hose AH 16 Y	358.570.001
Air Hose AH 16 B	358.570.002
Air Hose AH 16 R	358.570.003
Air Hose AH 32 R	358.570.004
Air Hose AH 32 B	358.570.005
Air Hose AH 32 Y	358.570.006

Standard Supplied With

- Carrying straps
- Flexible integrated dust cap on air inlet



